

TRICKLE VENT PERFORMANCE DATA

Geometrical Area (mm²)	Vent Type	Equivalent Area (mm²)
2000	Slimline 2000+Hood	1430
2000	Slimline 2000 Mk2+Hood	1390
4000	Slimline 4000+Hood	2670
4000	Slimline 4000 Mk2+Hood	2830
2000	Standard 2000+Hood	1380
2000	Standard 2000+Grille	1360
2000	Standard 2000+Grille+Hood	1120
4000	Standard 4000+Hood	2580
4000	Standard 4000+Grille	2700
4000	Standard 4000+Grille+Hood	2030
2000	Modular 2000+Hood	1293
2000	Modular 2000+Grille	1485
4000	Modular 4000+Hood	2585
4000	Modular 4000+Grille	2970
6000	Modular 6000+Hood	3878
6000	Modular 6000+Grille	4455
8000	Modular 8000+Hood	5170
8000	Modular 8000+Grille	5940

ACOUSTIC VALUES

Type/Condition	D.n.e.w
2000 Slimline Open	35.0
2000 Slimline Closed	37.0
4000 Slimline Open	32.0
4000 Slimline Closed	34.0
2000 Slimline Mk2 Open	36.0
2000 Slimline Mk 2 Closed	44.0
4000 Slimline Mk2 Open	32.0
4000 Slimline Mk 2 Closed	35.0
2000 Standard Open	34.0
2000 Standard Closed	39.0
4000 Standard Open	31.0
4000 Standard Closed	36.0
2000 Open	34.0
2000 Closed	40.0
4000 Open	31.0
4000 Closed	37.0
6000 Open	29.0
6000 Closed	35.0
8000 Open	28.0
8000 Closed	34.0